

THE INVENTION CLAIMED IS

1. In a warehouse safety device for preventing objects  
5 from falling out of a pallet rack having a frame with a  
number of shelves for palleted material, a safety netting  
attached to a front face of the pallet rack and strung  
around its perimeter by suspension cables, the improvement  
comprising:

10 an offset bracket for attachment to the pallet  
rack and providing anchoring points for said suspension  
cables; and

a U-channel section disposed in the offset bracket  
that provides for a two sided attachment to a vertical frame  
15 part of said pallet rack; and

a plurality of attachment points disposed in the  
offset bracket that provides for at least two different  
offsets of said netting from a front face of said pallet  
rack.

20 2. The device of claim 1, wherein:

the offset bracket further comprises a box end  
section, a first set of anchor holes on both vertical sides  
of said box section that provide for horizontal ones of said  
25 netting suspension cables, and a second set of anchor holes  
on both horizontal sides of said box section that provide  
for vertical ones of said netting suspension cables.

3. The device of claim 2, wherein:

30 said box end section is such that said first set  
of anchor holes are placed from the end differently from  
said second set of anchor holes and provides for criss-  
crossing of said suspension cables within.

4. An offset bracket for a pallet rack safety netting, comprising:

a box end section;

5 a first set of anchor holes on both vertical sides of the box section that provide for horizontal ones of netting suspension cables;

a second set of anchor holes on both horizontal sides of the box section that provide for vertical netting suspension cables;

10 a pair of arms extending to form a U-channel from the box section; and

a plurality of attachment points disposed in the pair of arms that provide for a selection of distances with which a safety netting secured by the suspension cables is offset from a front face of said pallet rack.

5. An offset bracket, comprising:

an end section;

20 a first set of holes on both vertical sides of the end section;

a second set of holes on both horizontal sides of the end section;

25 a pair of arms extending to form a U-channel from the box section; and

a plurality of attachment points disposed in the pair of arms that provide for a selection of distances with which said offset bracket is secured to a support member.